

BeveLED Mini Performance Summary



BeveLED Mini Downlight

Beam options: 25° 35° 50°	14 Watts		20 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	64	52	53	43
Source Lumens	1100	825	1500	1050
Delivered Lumens	900	725	1150	925
Color Consistency	2-Step MacAdam Ellipse			

Performance based on 3000K

BeveLED Mini Adjustable

Beam options: 10° 25°	14 Watts		20 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	45	36	37	30
Source Lumens	1100	825	1500	1050
Delivered Lumens	625	500	800	650
Center Beam Candle Power (10°)	7825	6250	10050	8025
Color Consistency	2-Step MacAdam Ellipse			

Performance based on 3000K

BeveLED Mini Wall Wash

	14 Watts		20 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	46	38	40	31
Source Lumens	1100	825	1500	1050
Delivered Lumens	650	525	850	675
Color Consistency	2-Step MacAdam Ellipse			

Performance based on 3000K

COMPARE

	BeveLED Mini		MR-16
	20 Watts		50 Watts
Color Rendering Index	80+ CRI	90+ CRI	99+ CRI
Lumens per Watt	37	30	19
Source Lumens	1500	1050	912
Delivered Lumens	800	650	804
Center Beam Candle Power (10°)	10050	8025	9056

