


# BeveLED 2.1 Performance Summary



## BeveLED 2.1 Downlight

Beam options: 25° 50° 90°	9 Watts		12 Watts		16 Watts		24 Watts		33 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	100	74	93	73	93	72	86	67	77	62
Source Lumens	1150	900	1300	1025	1725	1350	2400	1875	3025	2350
Delivered Lumens	850	675	1125	875	1475	1150	2050	1600	2600	2025
Color Consistency	 2-Step MacAdam Ellipse									


Performance based on 3000K

### REPLACES

32W CFL	42W CFL	90W PAR 38
80 CRI	82 CRI	99 CRI
40	39	13
2400	3200	1310
1404	2005	1159



## BeveLED 2.1 Adjustable

Beam options: 10° 25°	9 Watts		12 Watts		16 Watts		24 Watts		33 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	95	74	81	64	81	64	75	59	64	53
Source Lumens	1150	900	1300	1025	1725	1350	2400	1875	3025	2350
Delivered Lumens	850	675	975	750	1300	1025	1800	1400	2250	1750
Color Consistency	 2-Step MacAdam Ellipse									


Performance based on 25° beam, 3000K

### REPLACES

32W CFL	42W CFL	90W PAR 38
80 CRI	82 CRI	99 CRI
40	39	13
2400	3200	1310
1404	1872	1159
13000	19000	20000



## BeveLED 2.1 Wall Wash

	9 Watts		12 Watts		16 Watts		24 Watts		33 Watts	
Color Rendering Index	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI	80+ CRI	90+ CRI
Lumens per Watt	74	65	63	57	63	56	58	52	52	47
Source Lumens	1150	900	1300	1025	1725	1350	2400	1875	3025	2350
Delivered Lumens	675	575	750	750	1000	900	1400	1250	1750	1550
Color Consistency	 2-Step MacAdam Ellipse									

Performance based on 3000K